

PRODUCT DATA SHEET

FC11 Cable Pit

Description

FC11 Cable Pit – Glass Fibre Reinforced Concrete (GFRC) Cable Pit

Dimensions (Nominal)

| Measurement | Length | Width | Depth |
|-------------------------------|--------|-------|-------|
| Overall Dimension | 2050 | 575 | 900 |
| Inside Lid Recess | 1980 | 505 | |
| Internal Wall (Top) | 1910 | 455 | |
| Internal Base (Bottom) | 1800 | 340 | |



Specification

| Duty | Class | Rating | Weight |
|---------------------------|-------|----------|--------|
| [SD] Standard Duty | A | 330kgs | 253 |
| [LD] Light Duty | A+ | | 284.2 |
| [MD] Medium Duty | B | 2,670kgs | 317.8 |
| [HD] Heavy Duty | C & D | 8,000kgs | 521 |

Additional Product Information

For further product information please contact FCI.

All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of FCI products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to ensure that each product is fit for its intended purpose and that the actual conditions are suitable. FCI pursues a policy of continuous product development and reserves the right to amend specifications without notice.